



Features:

EUROLITE LED IP PAR 14x8W QCL

Weather-proof (IP65) spotlight with 4in1 QCL RGBW color mixing and frost filters

- 14 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With double bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397749328

Weight: 66,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER UG-1 Universal Devicecase

Trunk case with castors

- With 4 device compartments
- Steel ball corner
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

Technical specifications:

Weight: 63.47 kg

EUROLITE LED IP PAR 14x8W QCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle (1/2 peak):	15° 27° 30° 60°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome LCD display
Color:	Black

Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm
Weight:	7.15 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER UG-1 Universal Devicecase

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	27.5 cm x 27.5 cm x 29 cm
Accessory compartment:	10 cm x 60 cm x 31.5 cm
Dimensions:	Width: 75 cm Depth: 64.5 cm Height: 57 cm
Weight:	28.30 kg

Scope of delivery:

4 x EUROLITE LED IP PAR 14x8W QCL

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery
3 x frost filter
1 x XLR cable
2 x knurled screw

1 x ROADINGER UG-1 Universal Devicecase

1 x case