



List price: 2378.81 €

incl. 19% VAT.

Features:

EUROLITE LED IP Mega PIX Strobe 714 SWING

Outdoor spotlight (IP65) with tilt motor for strobe, blinder and matrix effects

- 126 LEDs 3 W SMD 3535 cold white (CW)
7 segments controlled separately
- 588 LEDs 0.25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
14 segments controlled separately
- Positioning within 200° TILT
- Dimmer
- Color macros adjustable; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; color animations with two adjustable colors
- Ambient effect; strobe effect; Blinder effect
- 46 integrated show programs
- The device is cooled by cooling fan at the base; temperature-controlled fan at the head
- Control via DMX; RDM; stand-alone; master/slave function
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 120°
- With omega bracket
- Multicolor TFT display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397756340

Weight: 55,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase PRO 2x IP Mega SWING with wheels

Trunk case with castors, PRO version

- With 2 device compartments
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Branded hardware
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 2 x castors with 2 locking brakes Ø 100 mm

Technical specifications:

Weight: 50.40 kg

EUROLITE LED IP Mega PIX Strobe 714 SWING

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	365 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	126 x 3 W SMD 3535 cold white (CW) 588 x 0.25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	200° positioning auto position correction (feedback)
Flash rate:	0.5 - 17 Hz
Equipment:	Dimmer
DMX channels:	8; 9; 11; 12; 17; 18; 71
DMX input:	3-pin XLR (M) mounting version IP 1 x 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP
Cooling:	1 x cooling fan at the base 2 x temperature-controlled fan at the head
Control:	DMX; RDM; stand-alone; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4100 Hz
Beam angle:	120°

Beam angle (1/2 peak):	Matrix effect 120°
Beam angle (1/10 peak):	Matrix effect 170°
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor TFT display
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 52.5 cm Depth: 14.0 cm Height: 33.5 cm
Weight:	12.85 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase PRO 2x IP Mega SWING with wheels

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	2 x castors with 2 locking brakes Ø 100 mm
Material:	Plywood multi-layer glued, 9.5 mm, laminated
Color:	Black
Device compartment:	53 cm x 14.5 cm x 33.5 cm
Accessory compartment:	55 cm x 15 cm x 33.5 cm
Dimensions:	Width: 60 cm Depth: 61.5 cm Height: 61 cm
Weight:	24.70 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 2 x omega bracket