



Features:

EUROLITE LED IP Mega PIX Strobe 714 SWING

Outdoor spotlight (IP65) with tilt motor for strobe, blinder and matrix effects

- 126 LEDs 3 W SMD 3535 cold white (CW)
7 segments controlled separately
- 588 LEDs 0.25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
14 segments controlled separately
- Positioning within 200° TILT
- Dimmer
- Color macros adjustable; Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; color animations with two adjustable colors
- Ambient effect; strobe effect; Blinder effect
- 46 integrated show programs
- The device is cooled by cooling fan at the base; temperature-controlled fan at the head
- Control via DMX; RDM; stand-alone; master/slave function
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 120°
- With omega bracket
- Multicolor TFT display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397756340

Weight: 55,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase PRO 2x IP Mega SWING with wheels

Trunk case with castors, PRO version

- With 2 device compartments
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Branded hardware
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 2 x castors with 2 locking brakes Ø 100 mm

Technical specifications:

Weight: 50.40 kg

EUROLITE LED IP Mega PIX Strobe 714 SWING

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 365 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Cable construction: | 3 x 1.5 mm ² H07RN-F |
| Power output: | IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 126 x 3 W SMD 3535 cold white (CW) 588 x 0.25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 200° positioning auto position correction (feedback) |
| Flash rate: | 0.5 - 17 Hz |
| Equipment: | Dimmer |
| DMX channels: | 8; 9; 11; 12; 17; 18; 71 |
| DMX input: | 3-pin XLR (M) mounting version IP 1 x 5-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP |
| Cooling: | 1 x cooling fan at the base 2 x temperature-controlled fan at the head |
| Control: | DMX; RDM; stand-alone; master/slave function |
| Fixtures available for: | Light Captain |
| Projection: | Flicker-free |
| PWM frequency: | 4100 Hz |
| Beam angle: | 120° |

| | |
|-------------------------|---|
| Beam angle (1/2 peak): | Matrix effect 120° |
| Beam angle (1/10 peak): | Matrix effect 170° |
| Housing color: | Black |
| Attachment system: | 2x omega bracket |
| Display type: | Multicolor TFT display |
| Carrying handle: | 2 pc/pcs |
| Transport aid: | 4 x rubber feet |
| Use of brands: | Built with SEETRONIC connector |
| Material: | Aluminum casting |
| Dimensions: | Width: 52.5 cm Depth: 14.0 cm Height: 33.5 cm |
| Weight: | 12.85 kg |
| Noise classification: | Class 2 (slight noise) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase PRO 2x IP Mega SWING with wheels

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs with shut-off function |
| Transport aid: | 2 x castors with 2 locking brakes Ø 100 mm |
| Material: | Plywood multi-layer glued, 9.5 mm, laminated |
| Color: | Black |
| Device compartment: | 53 cm x 14.5 cm x 33.5 cm |
| Accessory compartment: | 55 cm x 15 cm x 33.5 cm |
| Dimensions: | Width: 60 cm Depth: 61.5 cm Height: 61 cm |
| Weight: | 24.70 kg |

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 2 x omega bracket