



**List price: 1783.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED TMH-H380 Beam/Wash/Flower Effect

Moving washlight with 19 x 20W RGLB LEDs, rotating flower effect and pixel control

- 19 LEDs 20 W 4in1 RGLB (homogenous color mix) LEDs controlled separately
- Positioning within 540° PAN, 215° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven; lens rotation
- Pulse-width modulation adjustable; Dimmer; color blend stepless; colors preset
- Wash effect; flower effect; beam effect
- The device is cooled by cooling fan at the base; temperature-controlled fan at the head
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- With a beam angle of 1° - 35°
- With omega bracket
- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended
- Flicker-free

### Logistic

EAN / GTIN: 4026397758238

Weight: 47,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

## ROADINGER Flightcase 2x TMH-H380 with wheels

### Trunk case

- With 2 device compartment
- With 1 accessory compartment
- Interior with foam padding<BR>cover with foam padding
- Aluminium profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes

## Technical specifications:

---

Weight: 45.30 kg

---

## EUROLITE LED TMH-H380 Beam/Wash/Flower Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	270 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	19 x 20 W 4in1 RRGBL (homogenous color mix)
Max. TILT movement:	215° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Zoom motor driven; lens rotation
DMX channels:	18; 30; 94
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	1 x cooling fan at the base 2 x temperature-controlled fan at the head
Control:	Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free

DMX fail mode:	Zero values; hold
Beam angle:	1° - 35°
Beam angle (1/2 peak):	1 - 21°
Beam angle (1/10 peak):	6 - 35°
Illuminance in Lux (lx):	Narrow red (R) 1m: 13251 lx, 3m: 5839 lx, 6m: 1772 lx Narrow green (G) 1m: 33878 lx, 3m: 14512 lx, 6m: 4482 lx Narrow blue (B) 1m: 6854 lx, 3m: 2372 lx, 6m: 831 lx Narrow lime 1m: 42876 lx, 3m: 18212 lx, 6m: 5554 lx Narrow all 1m: 86946 lx, 3m: 35241 lx, 6m: 11092 lx Wide red (R) 1m: 3735 lx, 3m: 458 lx, 6m: 119 lx Wide green (G) 1m: 9051 lx, 3m: 1106 lx, 6m: 289 lx Wide blue (B) 1m: 1639 lx, 3m: 204 lx, 6m: 54 lx Wide lime 1m: 11875 lx, 3m: 1430 lx, 6m: 381 lx Wide all 1m: 23450 lx, 3m: 2819 lx, 6m: 742 lx
Lamp life:	20000 h
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor LCD display
Control elements:	Power switch
USB port:	Type A
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø10mm
Material:	Metal
Dimensions:	Width: 34.0 cm Depth: 22.5 cm Height: 34.5 cm
Weight:	11.75 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x TMH-H380 with wheels**

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes
Color:	Black, laminated
Device compartment:	25.5 cm x 35 cm x 46 cm
Accessory compartment:	8 cm x 35 cm x 23 cm

Inside dimensions:	61.5 cm x 35 cm x 46 cm
Material thickness:	9 mm
Dimensions:	Width: 66 cm Depth: 40 cm Height: 66 cm
Weight:	18.65 kg

### **Scope of delivery:**

---

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket