



Features:

EUROLITE LED IP TMH-W285 Hypno Moving Head Wash

Weather-proof moving washlight with RGBW LEDs, backlighting via RGB hypno LEDs and zoom

- 19 LEDs 15 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
3 segments controlled separately
- 72 LEDs 0.12 W SMD 2528 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 260° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Dimmer; Dimmer speed (step response) adjustable; color blend stepless; color macros; colors preset
- Wash effect; beam effect
- The device is cooled by cooling fan at the head
- Control via stand-alone; DMX; RDM; master/slave function
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 2° - 48°
- With omega bracket
- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 4 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane

Logistic

EAN / GTIN: 4026397760675

Weight: 70,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; rental; restaurants, bars and hotels; theater
- Application possibility: Standing; suspended
- Fixtures available for Light Captain

ROADINGER Flightcase PRO 2x IP TMH-W285 with wheels

Trunk case with castors, PRO version

- With 2 device compartments
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- High-quality workmanship with plywood multi-layer glued 9.5 mm, black
- PENN Hardware

Technical specifications:

Weight:	68.45 kg
---------	----------

EUROLITE LED IP TMH-W285 Hypno Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	195 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	19 x 15 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 72 x 0.12 W SMD 2528 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	260° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1.3 - 10.6 Hz
Equipment:	Zoom motor driven
DMX channels:	18; 26
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP
Cooling:	1 x cooling fan at the head

Control:	Stand-alone; DMX; RDM; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	26000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	2° - 48°
Beam angle (1/2 peak):	2 - 30°
Beam angle (1/10 peak):	8 - 48°
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor LCD display
Status LED:	DMX, fault
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø11mm
Use of brands:	Built with SEETRONIC connector
Material:	Plastic
Dimensions:	Width: 38.8 cm Depth: 25.7 cm Height: 49.1 cm
Weight:	15.40 kg
Noise classification:	Class 2 (slight noise) depending on mode used
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase PRO 2x IP TMH-W285 with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	PENN Hardware
Material:	Plywood multi-layer glued, 9.5 mm
Color:	Black
Inside dimensions:	63.5 cm x 62.5 cm x 44.5 cm
Accessory compartment:	15 cm x 62.5 cm x 44.5 cm
Dimensions:	Width: 65 cm Depth: 62.6 cm Height: 73 cm
Weight:	32.20 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket