

EUROLITE LED IP PFE-40 CW/WW 25-50°

Weather-proof spotlight (IP65), 40 W COB LED, variable color temperature, CRI >90, RDM

Art. No.: 40001706

GTIN: 4026397718676



Features:

- 4 shutter blades
- Dimmable
- 1 LED 40 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Zoom manual; focus manual
- Dimmer electronic; Dimmer speed (step response) adjustable; pulse-width modulation variable
- Strobe effect
- Control via stand-alone; master/slave function; DMX; RDM
- Fixtures available for Light J; Light Captain
- With a beam angle of 25° - 50°
- Variable color temperature 2700 K - 6000 K
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Very quiet working noise
- For application areas such as: Architecture; stage; wedding/gala/events; Trade fair and shop fitting; theater
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397718676

Weight: 4,50 kg

Length: 0.44 m

Width: 0.21 m

Height: 0.23 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 30 W

IP classification: IP65

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	1 x 40 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Equipment:	Zoom manual; focus manual
DMX channels:	1; 2; 3; 6
DMX input:	1 x 3-pin XLR (M) mounting version IP
Control:	Stand-alone; master/slave function; DMX; RDM
Fixtures available for:	Light'J; Light Captain
Beam angle:	25° - 50°
Beam angle (1/2 peak):	25 - 50°
Beam angle (1/10 peak):	25 - 50°
Color temperature:	2700K - 6000K adjustable
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 34.5 cm Width: 15.5 cm Height: 28.5 cm
Weight:	3.95 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Gobos:	Outside diameter 37.5mm Image diameter 25mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device
 1 x gobo holder
 1 x filter frame
 1 x user manual
 1 x power cord
 1 x adapter cable
 1 x safety bond