

EUROLITE LED PFE-60 WW/CW Profile Spot 9-25°

Profile spotlight, 60 W WW/CW LED, manual zoom, shutter blades, CRI>90

Art. No.: 40001721

GTIN: 4026397716658



List price: 546.21 €

incl. 19% VAT.

Features:

- 1 powerful LED 60 W COB (chip-on-board) CW/WW
- Zoom manual; focus manual
- Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; RDM
- Preprogrammed in Light Captain
- Flicker-free
- Variable color temperature 3200 K - 5600 K
- Very high color rendering index (CRI)
- With mounting bracket
- Multicolor OLED display
- For application areas such as: Stage; theater; installation; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x gobo holder, 1 x user manual

Logistic

EAN / GTIN: 4026397716658

Weight: 3,95 kg

Length: 0.49 m

Width: 0.21 m

Height: 0.22 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 60 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) CW/WW
Equipment:	Zoom manual; focus manual
DMX channels:	2; 5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; RDM
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	9 - 25°
Color temperature:	3200K - 5600K adjustable
Color rendering index (CRI):	97 Ra
Lamp life:	50000 h
Luminous flux:	4500 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	Multicolor OLED display
Material:	Aluminum casting; metal
Dimensions:	Length: 42,5 cm Width: 16,0 cm Height: 25,5 cm Diameter: Ø 11,5 cm
Weight:	3,38 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	F
EPREL-Nr:	1597557
Mounting bracket	
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, 3 mm
Gobo holder	
Gobos:	Outside diameter 37mm Image diameter 25mm
Material:	Aluminum, 0,5 mm; plastic
Dimensions:	Diameter: Ø 3 cm