

EUROLITE LED PLL-384 RGB/WW Panel

DMX-controlled surface light with RGB/WW color mixing, QuickDMX port, frost filter and barn doors

Art. No.: 40001893

GTIN: 4026397717792



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 240 LEDs 1.5 W SMD 5054 R/G/B (homogenous color mix)
- 144 LEDs 1 W SMD 5054 warm white (WW)
- White balance adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; color change adjustable; color fade adjustable; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; master/slave function; quick select potentiometer for brightness and preset color; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; theater; rental; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397717792

Weight: 4,10 kg

Length: 0.37 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	160 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	240 x 1.5 W SMD 5054 R/G/B (homogenous color mix) 144 x 1 W SMD 5054 warm white (WW)
Flash rate:	0.8 - 22 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; master/slave function; quick select potentiometer for brightness and preset color; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Illuminance in Lux (lx):	Narrow red (R) 1m: 609 lx, 3m: 73 lx, 6m: 21 lx Narrow green (G) 1m: 1250 lx, 3m: 157 lx, 6m: 46 lx Narrow blue (B) 1m: 254 lx, 3m: 31 lx, 6m: 9 lx Narrow warm white (WW) 1m: 1957 lx, 3m: 243 lx, 6m: 73 lx Narrow all 1m: 4046 lx, 3m: 506 lx, 6m: 149 lx Wide red (R) 1m: 458 lx, 3m: 59 lx, 6m: 17 lx Wide green (G) 1m: 1048 lx, 3m: 137 lx, 6m: 41 lx Wide blue (B) 1m: 235 lx, 3m: 31 lx, 6m: 9 lx Wide warm white (WW) 1m: 1552 lx, 3m: 203 lx, 6m: 61 lx Wide all 1m: 3283 lx, 3m: 429 lx, 6m: 127 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 34.7 cm Width: 13.1 cm

	Height: 21.1 cm
Weight:	3.73 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 2 x knurled screw