

EUROLITE LED PLL-432 CW/WW Panel

DMX-controlled surface light with 432 dual white LEDs, QuickDMX port and barn doors

Art. No.: 40001894

GTIN: 4026397700718



Features:

- 4 barn doors to avoid blinding the audience and for protection during transport
- Energy-saving, durable and environmentally friendly
- 432 LEDs SMD 2835 CW/WW
- Pulse-width modulation variable
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; quick select potentiometer for brightness and color temperature; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 120°
- Variable color temperature 2800 K - 6500 K
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; installation
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397700718

Weight: 5,15 kg

Length: 0.62 m

Width: 0.17 m

Height: 0.24 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
IP classification:	IP20
Protection class:	Protection class I
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	432 x SMD 2835 CW/WW
DMX channels:	2; 4; 6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; quick select potentiometer for brightness and color temperature; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	2800K - 6500K adjustable
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Cold white (CW) 1m: 919 lx, 3m: 124 lx, 6m: 38 lx Warm white (WW) 1m: 801 lx, 3m: 109 lx, 6m: 33 lx All 1m: 1681 lx, 3m: 228 lx, 6m: 69 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 60.3 cm Depth: 17.9 cm Height: 20.8 cm
Weight:	4.60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord