

EUROLITE LED PFE-250 3000K Profile Spot

PRO profile spotlight, warm white 250 W LED, zoom, shutter blades, CRI >90

Art. No.: 40001970

GTIN: 4026397610277



Features:

- 1 LED 250 W COB (chip-on-board) warm white (WW)
- Focus manual; zoom manual
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397610277

Weight: 14,35 kg

Length: 0.74 m

Width: 0.36 m

Height: 0.34 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version

Lamp type:	LED lamp
LED type:	1 x 250 W COB (chip-on-board) warm white (WW)
Equipment:	Focus manual; zoom manual
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Lamp life:	50000 h
Luminous flux:	18807 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 64.5 cm Width: 27 cm Height: 37.5 cm
Weight:	12.60 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Energy efficiency class (A - G):	F
EPREL-Nr:	1350653

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual
- 1 x power cord
- 1 x plug (male)