

## EUROLITE LED PFE-200 3000K Profile Spot

PRO profile spotlight, warm white 200 W LED, zoom, shutter blades, CRI >95

Art. No.: 40001975

GTIN: 4026397705409



### Features:

- 1 LED 200 W COB (chip-on-board) warm white (WW)
- Zoom manual; focus manual
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Flicker-free
- Very high color rendering index (CRI)
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397705409

Weight: 12,75 kg

Length: 0.74 m

Width: 0.36 m

Height: 0.35 m

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version

Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	3.5 - 29 Hz
Equipment:	Zoom manual; focus manual
DMX channels:	3
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	2300 Hz
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Color temperature:	3157K
Color rendering index (CRI):	98 Ra
Lamp life:	15000 h
Luminous flux:	10188 lm
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 61.8 cm Width: 33.1 cm Height: 36.2 cm
Weight:	11.10 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Energy efficiency class (A - G):	F
EPREL-Nr:	1271171

### Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x plug (male)
- 1 x filter frame