

EUROLITE ML-56 CDM Multi Lens Spot sil

Spot for CDM-T 150 discharge lamp with 4 lenses/beam angles

Art. No.: 41600130

GTIN: 4026397398823



Features:

- Spot with 4 exchangeable lenses (VNSP, NSP, MFL and WFL)
- Light output of a conventional PAR 56 spot with less power consumption
- High-quality die-cast housing for highest stability
- High-quality aluminum reflector
- The device is cooled by passive convection cooling
- Control via plug and play
- For application areas such as: Trade fair and shop fitting

Logistic

EAN / GTIN: 4026397398823

Weight: 7,30 kg

Length: 0.28 m

Width: 0.28 m

Height: 0.52 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	155 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	0.85 m
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Base:	G-12
Lamp type:	Discharge lamp
Color generation:	Via color filter frame (optional)
Cooling:	Passive convection cooling

Control:	Plug and play
Beam angle (1/2 peak):	NSP 20° x 36° MFL 21° x 36° WFL 30° x 53° VNSP 15° x 36°
Housing color:	Silver
Dimensions:	Width: 28 cm Depth: 22 cm Height: 40 cm
Weight:	6.65 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device
1 x filter frame
4 x lens
1 x user manual