

EUROLITE LED KKL-30 Floodlight 4100K black

30 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600468

GTIN: 4026397646917



Features:

- Inclination angle of the LED head manually adjustable
 - Unique design
 - Easy mounting via screw clamp
 - For tabletops with up to 40 mm strength
 - 1 LED 30 W COB (chip-on-board) neutral white (NW)
 - The device is cooled by passive convection cooling
 - Control via plug and play
 - With a beam angle of 60°
 - Various versions available
 - For application areas such as: Decoration; advertisement/Shop window; Trade fair and shop fitting
 - Silent operation
 - Application possibility: Suspended; wall mounting
- knurled screw**
- M10 thread

Logistic

EAN / GTIN: 4026397646917

Weight: 0,95 kg

Length: 0.61 m

Width: 0.14 m

Height: 0.05 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) neutral white (NW)
Inclination angle:	90 °
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	60°
Beam angle (1/2 peak):	60°
Beam angle (1/10 peak):	106°
Color temperature:	4100K
Illuminance in Lux (lx):	1m: 861 lx, 3m: 133 lx, 6m: 40 lx
Luminous flux:	1769 lm
Housing color:	Black
Dimensions:	Length: 52 cm Width: 13.5 cm Depth: 8.5 cm
Weight:	0.86 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1106797
Thread:	M10 thread x 60 mm
Material:	Metal, 1.5 mm
Color:	Silver
Dimensions:	Diameter: Ø 2 cm

Scope of delivery:

- 1 x spotlight
- 1 x knurled screw
- 1 x plate
- 1 x user manual