

EUROLITE LED KKL-30 Floodlight 4100K white

30 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600469

GTIN: 4026397646931



Features:

- Inclination angle of the LED head manually adjustable
- Unique design
- Easy mounting via screw clamp
- For tabletops with up to 40 mm strength
- 1 LED 30 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 59°
- Good color rendering index (CRI)
- Various versions available
- For application areas such as: Decoration; advertisement/Shop window; Trade fair and shop fitting
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397646931

Weight: 0,99 kg

Length: 0.60 m

Width: 0.14 m

Height: 0.05 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05VV-F

Cable length:	Approx. 1.2 m
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) neutral white (NW)
Inclination angle:	90 °
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	59°
Beam angle (1/10 peak):	106°
Color temperature:	4100K
Color rendering index (CRI):	83 Ra
Illuminance in Lux (lx):	1m: 1339 lx, 3m: 144 lx, 6m: 43 lx
Luminous flux:	1796 lm
Housing color:	White
Dimensions:	Length: 62 cm Width: 13.5 cm Depth: 8.4 cm
Weight:	0.90 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Energy efficiency class (A - G):	G
EPREL-Nr:	1023937
Thread:	X 60 mm
Material:	Metal, 1.5 mm
Color:	Silver
Dimensions:	Diameter: Ø 2 cm

Scope of delivery:

- 1 x spotlight
- 1 x knurled screw
- 1 x plate
- 1 x user manual