

## EUROLITE LED KKL-50 Floodlight 4100K white

50 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600474

GTIN: 4026397603286



### Description:

The Eurolite KKL-50 LED floodlight illuminates trade fair booths, shop windows, workshops and even weatherproof outdoor areas.

You can purchase the KKL-50 in three simple casing colors: black, white and silver.

### Features:

- Unique design
- For tabletops with up to 40 mm strength
- 1 LED 50 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Easy installation
- With a beam angle of 75°
- Very high color rendering index (CRI)
- Various versions available
- Silent operation
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting
- Application possibility: Suspended; wall mounting

### Logistic

EAN / GTIN: 4026397603286

Weight: 2,33 kg

Length: 0.65 m

Width: 0.21 m

Height: 0.11 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 50 W

|                                  |                                                  |
|----------------------------------|--------------------------------------------------|
| IP classification:               | IP20                                             |
| Power connection:                | Fixed power supply cord with safety plug         |
| Cable construction:              | 3 x 1.0 mm <sup>2</sup> H05RN-F                  |
| Cable length:                    | Approx. 0.8 m                                    |
| Lamp type:                       | LED lamp                                         |
| LED type:                        | 1 x 50 W COB (chip-on-board) neutral white (NW)  |
| Cooling:                         | Passive convection cooling                       |
| Control:                         | Plug and play                                    |
| Setup:                           | Easy installation                                |
| Beam angle:                      | 75°                                              |
| Beam angle (1/2 peak):           | 75°                                              |
| Beam angle (1/10 peak):          | 125°                                             |
| Color temperature:               | 4100K                                            |
| Color rendering index (CRI):     | 90 Ra                                            |
| Illuminance in Lux (lx):         | 1m: 2260 lx, 3m: 228 lx, 6m: 65 lx               |
| Luminous flux:                   | 3769 lm                                          |
| Housing color:                   | White                                            |
| Dimensions:                      | Length: 64 cm<br>Width: 20.5 cm<br>Depth: 8.5 cm |
| Weight:                          | 2.00 kg                                          |
| Noise classification:            | Class 0 (no noise at all)                        |
| Energy efficiency class (A - G): | G                                                |
| EPREL-Nr:                        | 1273342                                          |

## Scope of delivery:

1 x spotlight  
 1 x knurled screw  
 1 x plate  
 1 x user manual