

EUROLITE LED KKL-70 Floodlight 4200K black

70 W LED floodlight with extension arm and screw terminal for fixation

Art. No.: 41600478

GTIN: 4026397750546



Features:

- Unique design
- Inclination angle of the LED head manually adjustable
- Easy mounting via screw clamp
- For tabletops with up to 40 mm strength
- 1 LED 70 W COB (chip-on-board) neutral white (NW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Flicker-free
- With a beam angle of 70°
- Very high color rendering index (CRI)
- Various versions available
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; decoration; advertisement/Shop window
- Silent operation
- Application possibility: Wall mounting

Logistic

EAN / GTIN: 4026397750546

Weight: 1,90 kg

Length: 0.66 m

Width: 0.21 m

Height: 0.10 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	72 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	0.8 m

Lamp type:	LED lamp
LED type:	1 x 70 W COB (chip-on-board) neutral white (NW)
Inclination angle:	210 °
Cooling:	Passive convection cooling
Control:	Plug and play
Projection:	Flicker-free
Beam angle:	70°
Beam angle (1/2 peak):	Wash effect 70° monochrome
Beam angle (1/10 peak):	120°
Color temperature:	4200K
Color rendering index (CRI):	93.2 Ra
Luminous flux maintenance:	93
Illuminance in Lux (lx):	Neutral white (NW) 1m: 728 lx, 3m: 138 lx, 6m: 42 lx
Luminous flux:	6300 lm
Housing color:	Black
Material:	Aluminum casting; metal
Dimensions:	Width: 19 cm Depth: 7 cm Height: 66 cm
Weight:	1.63 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F

Scope of delivery:

1 x spotlight
1 x mounting material
1 x plate
1 x user manual