

## EUROLITE LED THA-40PC Theater Spot bk

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

Art. No.: 41602080

GTIN: 4026397565218



### Features:

- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Fixtures available for LED PC-Control 512; Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 11° - 48°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window; theater
- Silent operation
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397565218

Weight: 4,30 kg

Length: 0.36 m

Width: 0.21 m

Heigh: 0.27 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 40 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	3100K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow 3m: 1656 lx, 6m: 424 lx Wide 3m: 348 lx, 6m: 103 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13.1 cm x 13.1 cm
Dimensions:	Length: 27.5 cm Width: 20.5 cm Depth: 25 cm
Weight:	3.85 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1 m
Material:	Aluminum, 1.5 mm; metal
Ring diameter:	Outside: 12.9 mm Inside: 10.9 mm
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0.8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10.5 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x spotlight
- 1 x barndoor
- 1 x filter frame
- 1 x user manual