

## EUROLITE LED THA-100F MK3 Theater Spot

Fresnel spotlight (fresnel lens), warm white 100 W LED, CRI >90, quiet, DMX

Art. No.: 41602127

GTIN: 4026397690453



### Features:

- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 8° - 55°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397690453

Weight: 9,30 kg

Length: 0.49 m

Width: 0.40 m

Height: 0.38 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 95 W

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version included
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	20 Hz
DMX channels:	1; 3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 40°
Beam angle (1/10 peak):	16 - 55°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Luminous flux:	5384 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting; metal
Dimensions:	Length: 35.0 cm Width: 31.5 cm Height: 39.5 cm
Weight:	7.15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243837
Cable construction:	3 x 1.5 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1.8 m
Diameter mounting holes:	5 x Ø13mm
Material:	Aluminum casting, 6 mm
Material:	Aluminum, 1 mm
Ring diameter:	Outside: 172 mm Inside: 150 mm

Dimensions: Width: 42.2 cm  
Height: 42.5 cm

---

Material: Aluminum, 1 mm

---

Dimensions: Width: 18.5 cm  
Height: 18.5 cm  
Diameter: Ø 15.2 cm

---

### **Scope of delivery:**

---

1 x spotlight  
1 x power cord  
1 x barndoor  
1 x filter frame  
1 x user manual