

EUROLITE LED THA-100F TRC Theater-Spot bk

Fresnel spot with 100 W white light LED, color rendering index (CRI) >90

Art. No.: 41602129

GTIN: 4026397689792



Features:

- Very high color rendering index (CRI)
- Very quiet working noise
- With a beam angle of 9° - 60°
- Flicker-free
- Control via quick select potentiometer for brightness; stand-alone
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Rugged metal housing
- With mounting bracket
- For application areas such as: Trade fair and shop fitting; video and photography; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397689792

Weight: 9,30 kg

Length: 0.48 m

Width: 0.40 m

Height: 0.38 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	120 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp

LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Cooling:	Temperature-controlled fan
Control:	Quick select potentiometer for brightness; stand-alone
Projection:	Flicker-free
Beam angle:	9° - 60°
Beam angle (1/2 peak):	9 - 40°
Beam angle (1/10 peak):	18 - 60°
Color temperature:	3200K
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 1m: 34719 lx, 3m: 4497 lx, 6m: 1151 lx Wide warm white (WW) 1m: 5802 lx, 3m: 700 lx, 6m: 210 lx
Luminous flux:	5833 lm
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Dimensions:	Length: 47 cm Width: 31 cm Height: 39 cm
Weight:	7.15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243857

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x filter frame
- 1 x barndoor