

## **EUROLITE LED THA-250F 2700K-6500K Theater Spot**

Fresnel spotlight, 250 W LED, variable color temperature, CRI >90, zoom

Art. No.: 41602135 GTIN: 4026397610833









# The article is no longer in our assortment.

### Features:

- 1 powerful LED 250 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Zoom motor driven; focus manual
- Dimmer electronic
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via DMX
- Preprogrammed in LED PC-Control 512; Light'J; Light Captain
- Flicker-free
- With a beam angle of 6° 46°
- Variable color temperature 2700 K 6500 K
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x XLR cable, 1 x plug (male)

#### **Technical specifications:**

| Power supply:      | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 200 W                  |
| IP classification: | IP20                   |

#### Logistic

EAN / GTIN: 4026397610833

Weight: 11,50 kg Length: 0.52 m Width: 0.33 m Heigth: 0.32 m

| Power connection:            | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
|------------------------------|--|
| Power output:                | 1 x P-Con (gray), mounting version   |
| Lamp type:                   | LED lamp   |
| LED type:                    | 1 x 250 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)                          |
| Equipment:                   | Zoom motor driven; focus manual  |
| DMX channels:                | 4; 5   |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version                        |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version                        |
| Cooling:                     | Temperature-controlled fan   |
| Control:                     | DMX  |
| Preprogrammed in:            | LED PC-Control 512; Light 'J; Light Captain  |
| Projection:                  | Flicker-free   |
| Beam angle:                  | 6° - 46°   |
| Beam angle (1/2 peak):       | 6 - 25°  |
| Beam angle (1/10 peak):      | 20 - 46°   |
| Color temperature:           | 2700K - 6500K adjustable   |
| Color rendering index (CRI): | 96 Ra  |
| Housing color:               | Black  |
| Attachment system:           | Mounting bracket   |
| Display type:                | LCD display  |
| Dimensions:                  | Length: 43,5 cm<br>Width: 27,5 cm<br>Height: 38,5 cm   |
| Weight:                      | 10,45 kg   |
| Noise classification:        | Class 2 (slight noise)   |
| Special product:             | Not designed for household room illumination   |
| Intended use:                | Show effect lighting   |