

EUROLITE LED THA-250F P.O. Theater-Spot

Pole operated fresnel spotlight (fresnel lens), warm white 200 W LED, CRI >90, quiet, DMX

Art. No.: 41602138

GTIN: 4026397735505



Features:

- Pole-operated bracket for pan & tilt control
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- Zoom motor driven
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Wash effect; strobe effect
- The device is cooled by temperature-controlled fan
- Control via quick select potentiometer for brightness and Zoom; DMX; RDM
- Flicker-free
- RDM For bidirectional communication over the DMX line
- DMX fail mode (hold; blackout)
- With a beam angle of 5° - 28°
- Very high color rendering index (CRI)
- TV spigot
- Monochrome LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Built with NEUTRIK connector
- For application areas such as: Theater; stage; wedding/gala/events; Trade fair and shop fitting; video and photography
- Very quiet working noise
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397735505

Weight: 15,50 kg

Length: 0.81 m

Width: 0.41 m

Height: 0.42 m

Technical specifications:

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 240 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power output: | PowerCON (gray), mounting version |
| Fuse: | 5 x 20 mm, T 3 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 200 W COB (chip-on-board) warm white (WW) |
| Flash rate: | 1.5 - 12 Hz |
| Equipment: | Zoom motor driven |
| Color generation: | Via color filter frame |
| DMX channels: | 3 |
| DMX input: | 3-pin XLR (M) mounting version 5-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Quick select potentiometer for brightness and Zoom; DMX; RDM |
| Projection: | Flicker-free |
| PWM frequency: | 3600 Hz |
| DMX features: | RDM For bidirectional communication over the DMX line |
| DMX fail mode: | Hold; blackout |
| Beam angle: | 5° - 28° |
| Beam angle (1/2 peak): | 5 - 28° |
| Beam angle (1/10 peak): | 12 - 28° |
| Color temperature: | 2800K |
| Color rendering index (CRI): | 91 Ra |
| Housing color: | Black |
| Attachment system: | TV spigot Ø 28mm |
| Display type: | Monochrome LCD display |
| Transport aid: | Rubber feet |
| Use of brands: | Built with NEUTRIK connector |
| Material: | Metal |
| Dimensions: | Length: 45.5 cm Width: 33.5 cm Height: 61.5 cm |
| Weight: | 11.90 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Special product: | Not designed for household room illumination |

Intended use:

Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x filter frame
- 1 x barndoor