

EUROLITE LED THA-450F Theater Spot

Fresnel spotlight (fresnel lens), 450-W-COB (chip-on-board)-LED 4in1 RGLB, extremely quiet, DMX

Art. No.: 41602200

GTIN: 4026397713954



Features:

- Variable color temperature 2400 K - 8500 K
- With a beam angle of 5° - 50°
- Zoom motor driven
- Very high color rendering index (CRI)
- Very quiet working noise
- Exact 16 bit resolution at Dimmer
- Flicker-free
- Control via stand-alone; DMX; RDM; rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- 1 LED 450 W COB (chip-on-board) 4in1 RGLB
- Color blend stepless; dimmer curves with adjustable response; Dimmer electronic; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Direct color selection for 117 preset colors
- Strobe effect
- Rugged metal housing
- Rubber-coated handle
- With mounting bracket
- Application possibility: Suspended; on stand
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography

Logistic

EAN / GTIN: 4026397713954

Weight: 12,10 kg

Length: 0.56 m

Width: 0.41 m

Height: 0.40 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	440 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 450 W COB (chip-on-board) 4in1 RGBL
Flash rate:	1 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	1; 2; 4; 7; 18
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	5° - 50°
Beam angle (1/2 peak):	5 - 40°
Beam angle (1/10 peak):	14 - 50°
Color temperature:	2400K - 8500K adjustable
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 37.0 cm Width: 33.9 cm Height: 39.9 cm
Weight:	9.45 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x barndoor
1 x filter frame