

EUROLITE LED PAR-64 COB 3000K 100W Zoom wh

PAR spot with warm white 100 W COB LED and manual zoom

Art. No.: 41603602

GTIN: 4026397694826



Features:

- Light performance comparable to a traditional 1000 W halogen spot light
- Homogeneous light distribution
- Very high color rendering index (CRI)
- Flicker-free
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Control via DMX
- Dimmer speed (step response) adjustable; pulse-width modulation variable; Gamma correction adjustable
- Strobe effect
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; video and photography; theater
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397694826

Weight: 4,80 kg

Length: 0.50 m

Width: 0.38 m

Height: 0.38 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version

Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2; 3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX
Fixtures available for:	Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle (1/10 peak):	15 - 48°
Color temperature:	3000K
Color rendering index (CRI):	90 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 3m: 14535 lx, 6m: 3666 lx Wide warm white (WW) 3m: 2134 lx, 6m: 614 lx
Housing color:	White
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 26 cm Depth: 43.5 cm Height: 37.5 cm
Weight:	3.80 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x XLR cable
 1 x filter frame
 1 x mounting bracket
 2 x knurled screw
 2 x washer