

# **EUROLITE IP Audience Blinder 2x100W LED COB RGB+WW**

Weather-proof audience blinder with 2x 100 W COB LED in RGB+warm white


Art. No.: 41604160 GTIN: 4026397718386











incl. 19% VAT.

### Features:

- 2 powerful LEDs 100 W COB (chip-on-board) 4in1 QCL RGB/WW<BR> LEDs controlled separately
- Color blend stepless; Dimmer electronic
- Strobe effect
- 3 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX
- Preprogrammed in Light Captain; Light'J; Colorchief
- Flicker-free
- With a beam angle of 28°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Mobile use; stage; rental
- Application possibility: Suspended; on stand

#### Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable

### **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W

## Logistic

EAN / GTIN: 4026397718386

Weight: 8,60 kg Length: 0.48 m Width: 0.30 m Heigth: 0.30 m

Protection class: Protection class I Power connection: Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) Power output:  1 x IP T-Con (F) mounting version Lamp type: LED lamp  LED type: 2 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW  Flash rate: 1 - 25 Hz  DMX channels: 4; 6; 8; 12  DMX input: 3-pin XLR (M) mounting version IP  DMX output: 3-pin XLR (F) mounting version IP  Cooling: Temperature-controlled fan  Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light' J; Colorchief  Projection: Flicker-free Beam angle: 28° Beam angle (1/12 peak): 28° Beam angle (1/10 peak): 75° Housing color: Black  Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination  Intended use: Show effect lighting	IP classification:	IP65
power supply cord with safety plug (provided)  Power output: 1 x IP T-Con (F) mounting version  Lamp type: LED lamp  LED type: 2 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW  Flash rate: 1 - 25 Hz  DMX channels: 4; 6; 8; 12  DMX input: 3-pin XLR (M) mounting version IP  DMX output: 3-pin XLR (F) mounting version IP  Cooling: Temperature-controlled fan  Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light 'J; Colorchief  Projection: Flicker-free  Beam angle: 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Protection class:	Protection class I
LED lamp  LED type: 2 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW  Flash rate: 1 - 25 Hz  DMX channels: 4; 6; 8; 12  DMX input: 3-pin XLR (M) mounting version IP  DMX output: 3-pin XLR (F) mounting version IP  Cooling: Temperature-controlled fan  Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light' J; Colorchief  Projection: Flicker-free  Beam angle: 28°  Beam angle (1/2 peak): 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Power connection:	
LED type:  2 x 100 W COB (chip-on-board) 4in1 QCL RGB/WW  Flash rate:  1 - 25 Hz  DMX channels:  4; 6; 8; 12  DMX output:  3-pin XLR (M) mounting version IP  DMX output:  3-pin XLR (F) mounting version IP  Cooling:  Temperature-controlled fan  Control:  Stand-alone; master/slave function; DMX  Preprogrammed in:  Light Captain; Light 'J; Colorchief  Projection:  Flicker-free  Beam angle:  28°  Beam angle (1/2 peak):  28°  Beam angle (1/10 peak):  75°  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Power output:	1 x IP T-Con (F) mounting version
RGB/WW  Flash rate: 1 - 25 Hz  DMX channels: 4; 6; 8; 12  DMX input: 3-pin XLR (M) mounting version IP  DMX output: 3-pin XLR (F) mounting version IP  Cooling: Temperature-controlled fan  Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light'J; Colorchief  Projection: Flicker-free  Beam angle: 28°  Beam angle (1/2 peak): 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Lamp type:	LED lamp
DMX channels:  4; 6; 8; 12  DMX input:  3-pin XLR (M) mounting version IP  Cooling:  Temperature-controlled fan  Control:  Stand-alone; master/slave function; DMX  Preprogrammed in:  Light Captain; Light'J; Colorchief  Projection:  Flicker-free  Beam angle:  28°  Beam angle (1/2 peak):  28°  Beam angle (1/10 peak):  T5°  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	LED type:	` ' '
DMX input:  3-pin XLR (M) mounting version IP  DMX output:  3-pin XLR (F) mounting version IP  Cooling:  Temperature-controlled fan  Control:  Stand-alone; master/slave function; DMX  Preprogrammed in:  Light Captain; Light'J; Colorchief  Projection:  Flicker-free  Beam angle:  28°  Beam angle (1/2 peak):  28°  Beam angle (1/10 peak):  75°  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Flash rate:	1 - 25 Hz
DMX output:  3-pin XLR (F) mounting version IP  Cooling:  Temperature-controlled fan  Control:  Stand-alone; master/slave function; DMX  Preprogrammed in:  Light Captain; Light'J; Colorchief  Projection:  Flicker-free  Beam angle:  28°  Beam angle (1/2 peak):  28°  Beam angle (1/10 peak):  75°  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	DMX channels:	4; 6; 8; 12
Cooling: Temperature-controlled fan  Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light'J; Colorchief  Projection: Flicker-free  Beam angle: 28°  Beam angle (1/2 peak): 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm	DMX input:	3-pin XLR (M) mounting version IP
Control: Stand-alone; master/slave function; DMX  Preprogrammed in: Light Captain; Light 'J; Colorchief  Projection: Flicker-free  Beam angle: 28°  Beam angle (1/2 peak): 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version IP
Preprogrammed in:  Light Captain; Light'J; Colorchief  Projection:  Flicker-free  Beam angle:  28°  Beam angle (1/2 peak):  Beam angle (1/10 peak):  T5°  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Cooling:	Temperature-controlled fan
Projection:  Beam angle:  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Control:	Stand-alone; master/slave function; DMX
Beam angle: 28°  Beam angle (1/2 peak): 28°  Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Preprogrammed in:	Light Captain; Light´J; Colorchief
Beam angle (1/2 peak):  Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak): 75°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Width: 40,3 cm	Beam angle:	28°
Housing color:  Attachment system:  Mounting bracket  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/2 peak):	28°
Attachment system:  Display type:  4 digit 7-segment LED display  Dimensions:  Width: 40,3 cm  Depth: 19,5 cm  Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/10 peak):	75°
Display type:  4 digit 7-segment LED display  Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Housing color:	Black
Dimensions:  Width: 40,3 cm Depth: 19,5 cm Height: 29,8 cm  Weight:  7,85 kg  Noise classification:  Class 2 (slight noise)  Legal specifications  Special product:  Not designed for household room illumination	Attachment system:	Mounting bracket
Depth: 19,5 cm Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Height: 29,8 cm  Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination	Dimensions:	Width: 40,3 cm
Weight: 7,85 kg  Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination		
Noise classification: Class 2 (slight noise)  Legal specifications  Special product: Not designed for household room illumination		Height: 29,8 cm
Legal specifications  Special product:  Not designed for household room illumination	Weight:	7,85 kg
Special product: Not designed for household room illumination	Noise classification:	Class 2 (slight noise)
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting