

EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

Art. No.: 41606200

GTIN: 4026397459838



Features:

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 60°

Logistic

EAN / GTIN: 4026397459838

Weight: 9,20 kg

Length: 0.43 m

Width: 0.41 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	275 W
Lamp type:	LED lamp
Flash rate:	1 - 20 Hz
DMX channels:	3; 16; 19

Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain
Beam angle (1/2 peak):	60°
Color temperature:	3200K
Housing color:	Black
Dimensions:	Width: 31.5 cm Depth: 34.5 cm Height: 34.5 cm
Weight:	8.20 kg
DMX channels:	3/16/19
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
Sound-control:	via built-in microphone
LED number:	16
LED type:	Array 20 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (W x D x H):	345 x 315 x 345 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:
