

EUROLITE LED Pixel Matrix Panel 2x5 RGB/WW

Matrix spotlight with RGB/WW LEDs, pixel control & macros for sequences

Art. No.: 41606355

GTIN: 4026397742503



List price: 451.01 €

incl. 19% VAT.

Features:

- Create sensational light effect surfaces by connecting several devices
- 10 powerful LEDs 12 W SMD 5050 4in1 QCL RGB/WW (homogenous color mix) LEDs controlled separately
- Dimmer electronic; color change; color fade; foreground color adjustable; background color adjustable; color macros adjustable
- Blinder effect; matrix effect; strobe effect
- 9 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); RDM; Art-Net; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light; master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 45°
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles; with bracket for floor use
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397742503

Weight: 5,80 kg

Length: 0.53 m

Width: 0.27 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	10 x 12 W SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0,4 - 11 Hz
DMX channels:	4; 10; 15; 40; 42
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); RDM; Art-Net; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light; master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
PWM frequency:	2900 Hz
DMX fail mode:	Hold; blackout
Beam angle:	45°
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	82°
Housing color:	Black
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Bracket for floor use
Display type:	Multicolor LCD display
USB port:	Type A
Diameter mounting holes:	3 x Ø10mm
Material:	Metal
Dimensions:	Width: 45,0 cm Depth: 13,5 cm Height: 20,3 cm
Weight:	5,00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting