

EUROLITE LED IP Atmo Blinder 9

Weather-proof blinder with pixel control and atmo cluster

Art. No.: 41606430

GTIN: 4026397714487



Features:

- Each of the 9 COB blinder LEDs is surrounded by 2 RGB segments for atmospheric light
- One RGB LED segment is directed towards the front, one towards the reflector
- 360 LEDs 0.2 W SMD 3528 3in1 R/G/B (homogenous color mix)
18 segments controlled separately
- 9 LEDs 24 W COB (chip-on-board) CW/WW (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response; white balance adjustable
- Atmospheric effect
- 15 integrated show programs
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; Art-Net; RDM; master/slave function
- Flicker-free
- With a beam angle of 20°
- Variable color temperature 1800 K - 6000 K
- With mounting bracket; with omega bracket
- Multicolor LCD display
- Mains input and output for power linking up to 4 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397714487

Weight: 15,00 kg

Length: 0.50 m

Width: 0.47 m

Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	330 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	360 x 0.2 W SMD 3528 3in1 R/G/B (homogenous color mix) 9 x 24 W COB (chip-on-board) CW/WW (homogenous color mix)
DMX channels:	13; 18; 72; 85
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX; Art-Net; RDM; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	58°
Color temperature:	1800K - 6000K adjustable
Housing color:	Black
Attachment system:	Mounting bracket 2x omega bracket
Display type:	Multicolor LCD display
Connections:	2 x RJ-45 (F) mounting version
Dimensions:	Width: 37.7 cm Depth: 20.5 cm Height: 38.4 cm
Weight:	13.65 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x XLR cable
2 x omega bracket