

EUROLITE LED PMC-8x30W COB RGB MFL

COB Performance Cluster with 25° beam angle

Art. No.: 41606450

GTIN: 4026397507805



The article is no longer in our assortment.

Features:

- Operable in stand-alone mode via control panel with LCD screen or in DMX mode
- Equipped with 8 x 30 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Functions: Static colors, RGB color mixture, automatic color change, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) controllable
- Adjustable white balance
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Ideal as floor spot via base for standing installation
- Locking possibility at the mounting bracket
- With barn doors
- Neutrik powerCON terminals for power linking up to 8 units
- 8 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via DMX; sound to light via microphone; RDM
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 25°

Logistic

EAN / GTIN: 4026397507805

Weight: 7,60 kg

Length: 0.41 m

Width: 0.24 m

Height: 0.29 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 220,00 W

IP classification: IP20

Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	8 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	3; 4; 5; 6; 12; 24; 28; 33
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; RDM
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle:	25°
Beam angle (1/2 peak):	25°
Beam angle (1/10 peak):	46°
Housing color:	Black
Dimensions:	Width: 35,8 cm Depth: 17,4 cm Height: 22,3 cm
Weight:	7,05 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting