

EUROLITE AKKU Bar-6 Entry QCL RGBW Bar

Battery-powered light effect bar with RGBW LEDs and IR remote control

Art. No.: 41700101

GTIN: 4026397689662



Features:

- Cordless, flexible and versatile
- 6 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 18°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397689662

Weight: 3,05 kg

Length: 0.56 m

Width: 0.15 m

Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|-------------------------|--|
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | T 0.5 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 22.2 V, 2200 mAh, 48.84 Wh |
| Battery pack: | Recharging time 3h |
| Lamp type: | LED lamp |
| LED type: | 6 x 8 W SMD 9080 4in1 RGBW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4; 4; 6; 8 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 18° |
| Beam angle (1/10 peak): | 35° |
| Housing color: | Black |
| Attachment system: | 2x mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 54.5 cm Depth: 13.8 cm Height: 15.7 cm |
| Weight: | 2.76 kg |
| Noise classification: | Class 0 (no noise at all) |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x device
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 2 x mounting bracket
 2 x knurled screw
 2 x washer