

EUROLITE AKKU PT-100/32 Pixel DMX Tube

Battery-powered and DMX-controllable pixel tube with RGB color mixing

Art. No.: 41700350

GTIN: 4026397693973



List price: 296.31 €

incl. 19% VAT.

Features:

- Rugged metal housing
 - Cordless, flexible and versatile
 - Battery operation up to 9h depending on program used
 - 96 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
32 segments controlled separately
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - 12 integrated show programs
 - Direct color selection for 17 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light Captain; Light´J
 - 4 digit 7-segment LED display
 - For application areas such as: Wedding/gala/events; party room; mobile use; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Standing; suspended; wall mounting
- Package contents**
- 1 x device, 1 x user manual, 1 x external mains adapter, 1 x stand, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397693973

Weight: 3,00 kg

Length: 1.05 m

Width: 0.10 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 13V DC
Pin configuration:	Inside + / outside -
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) Battery/battery pack
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 1,5h
LED type:	96 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 8; 48; 96
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Light´J
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 5 cm Depth: 12,7 cm Height: 100 cm
Weight:	2,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting