

## EUROLITE AKKU Slim Tube AIR Set

Art. No.: 41700400

4 battery-powered effect tubes with 32 pixels, AirW wireless system (2.4 GHz), remote control and bag

GTIN: 4026397739565



### Features:

- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Cordless, flexible and versatile
- Battery operation up to 8h depending on program used
- Integrated automatic charging of the battery
- 32 LEDs 0.25 W SMD 5050 3in1 TCL RGB<BR> LEDs controlled separately
- Frost filter
- Dimmer electronic; Energy-saving mode adjustable; color macros preset; program selection manual; color blend stepless; color selection adjustable; color fade adjustable; running light adjustable; effect speed adjustable speed; pulse effect adjustable speed
- Strobe effect
- 40 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; AirW; wireless remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional)
- Fixtures available for LED PC-Control 512
- Flicker-free
- AirW: operating range up to 70m with line-of-sight
- DMX fail mode (blackout; hold; full on)
- The article is delivered with practical transport bag
- 4 digit 7-segment LED display
- Charge status indicator
- 4 pieces per set
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels

### Logistic

EAN / GTIN: 4026397739565

Weight: 7,90 kg

Length: 1.57 m

Width: 0.23 m

Height: 0.18 m

Bulky product

- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

#### **remote control**

- Operating range up to 30m with line-of-sight

### **Technical specifications:**

|                         |                                                                                                                                          |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz<br>5V DC 1400 mA                                                                                                  |
| IP classification:      | IP20                                                                                                                                     |
| Protection class:       | Protection class III                                                                                                                     |
| Power connection:       | Mains input via USB C (W) mounting version<br>power supply cord with AC adapter (provided)                                               |
| Battery pack type:      | 1 x lithium ion 7.4 V, 2600 mAh, 19.24 Wh                                                                                                |
| Battery pack:           | Battery operation up to 8h depending on program used<br>Recharging time 5h                                                               |
| Lamp type:              | LED lamp                                                                                                                                 |
| LED type:               | 32 x 0.25 W SMD 5050 3in1 TCL RGB                                                                                                        |
| Flash rate:             | 0.5 - 30 Hz                                                                                                                              |
| Equipment:              | Frost filter                                                                                                                             |
| DMX channels:           | 4; 6; 10; 13; 19; 49                                                                                                                     |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                       |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                       |
| Cooling:                | Passive convection cooling                                                                                                               |
| Control:                | Stand-alone; DMX; AirW; wireless remote control;<br>master/slave function; sound to light via<br>microphone; QuickDMX via USB (optional) |
| Fixtures available for: | LED PC-Control 512                                                                                                                       |
| Projection:             | Flicker-free                                                                                                                             |
| Range:                  | AirW: range up to 70m with line-of-sight                                                                                                 |
| Carrier frequency:      | 2.4 GHz                                                                                                                                  |
| DMX fail mode:          | Blackout; hold; full on                                                                                                                  |
| Standing/fixation:      | Stand                                                                                                                                    |
| Beam angle (1/2 peak):  | 360°                                                                                                                                     |
| Housing color:          | Transparent                                                                                                                              |
| Attachment system:      | 1x Ø 10mm                                                                                                                                |
| Display type:           | 4 digit 7-segment LED display                                                                                                            |
| Display:                | Charge status indicator                                                                                                                  |
| Status LED:             | Charge status indicator; signal                                                                                                          |
| USB port:               | 1 x type C                                                                                                                               |
| Dimensions:             | Length: 151 cm<br>Width: 6 cm<br>Height: 5 cm<br>Diameter: Ø 3.25 cm                                                                     |
| Weight:                 | 7.00 kg                                                                                                                                  |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                |

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Battery:           | 1 x 12 V 23AE alkaline manganese built-in       |
| Range:             | Range up to 30m with line-of-sight              |
| Carrier frequency: | 433.92 MHz                                      |
| Dimensions:        | Length: 155 cm<br>Width: 20 cm<br>Height: 17 cm |
| Special product:   | Not designed for household room illumination    |
| Intended use:      | Show effect lighting                            |

### Scope of delivery:

4 x light effect  
4 x frost filter  
4 x stand  
1 x charger  
1 x remote control  
1 x battery  
1 x bag  
1 x user manual  
1 x declaration of conformity  
2 x adapter