

## EUROLITE AKKU Slim Tube AIR

Battery-powered effect tube with 32 pixels and AirW wireless system (2.4 GHz)

Art. No.: 41700401

GTIN: 4026397746334



### Features:

- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Cordless, flexible and versatile
- Battery operation up to 6h depending on program used
- Integrated automatic charging of the battery
- 32 LEDs 0.25 W SMD 5050 3in1 R/G/B<BR> LEDs controlled separately
- Frost filter
- Dimmer electronic; Energy-saving mode adjustable; color macros preset; program selection manual; color blend stepless; color selection adjustable; color fade adjustable; running light adjustable; effect speed adjustable speed; pulse effect adjustable speed
- Ambient effect
- 40 integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; AirW; wireless remote control (not included); master/slave function; sound to light via microphone; QuickDMX via USB (optional)
- Flicker-free
- AirW: operating range up to 70m with line-of-sight
- 4 digit 7-segment LED display
- Charge status indicator
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397746334

Weight: 1,85 kg

Length: 1.57 m

Width: 0.14 m

Height: 0.12 m

Bulky product

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1400 mA
Protection class:	Protection class III
Power connection:	Mains input via USB C (W) mounting version power supply cord for USB A mains connection
Battery pack type:	1 x lithium ion 7.4 V, 2600 mAh, 19.24 Wh
Battery pack:	Battery operation up to 6h depending on program used Recharging time 5h charging one battery
Lamp type:	LED lamp
LED type:	32 x 0.25 W SMD 5050 3in1 R/G/B
Flash rate:	0.5 - 30 Hz
Equipment:	Frost filter
DMX channels:	4; 6; 10; 13; 19; 49
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; AirW; wireless remote control (not included); master/slave function; sound to light via microphone; QuickDMX via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Range:	AirW: range up to 70m with line-of-sight
Carrier frequency:	2.4 GHz
DMX fail mode:	Blackout; hold; full on
Standing/fixation:	Stand
Beam angle (1/2 peak):	360°
Housing color:	Transparent
Attachment system:	1x Ø 10mm
Display type:	4 digit 7-segment LED display
Display:	Charge status indicator
Status LED:	Charge status indicator; signal
USB port:	1 x type C
Diameter mounting holes:	1 x Ø10mm
Dimensions:	Length: 151 cm Width: 5.3 cm Depth: 6 cm Diameter: Ø 3.25 cm
Weight:	1.08 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

- 1 x light effect
- 1 x frost filter
- 1 x stand
- 1 x USB cable
- 1 x user manual
- 1 x declaration of conformity