

EUROLITE AKKU TL-3 QCL RGB+UV Trusslight

Battery-powered trusslight with RGB+UV LEDs and IR remote control

Art. No.: 41700510

GTIN: 4026397683783



Features:

- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 8h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 4 W SMD 9080 4in1 RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 10°
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397683783

Weight: 1,38 kg

Length: 0.15 m

Width: 0.14 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class III
Power connection:	Battery/battery pack built-in Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	F 1 A fuse replaceable
Battery pack type:	1 x lithium ion 11.1 V, 2200 mAh, 24.42 Wh
Battery pack:	Battery operation up to 8h depending on program used Recharging time 2.5h
Lamp type:	LED lamp
LED type:	3 x 4 W SMD 9080 4in1 RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	10°
Beam angle (1/10 peak):	33°
Housing color:	Black matte
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 12.22 cm Depth: 10.8 cm Height: 14.3 cm
Weight:	1.26 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery