

EUROLITE AKKU UP-4 HCL Spot WDMX bk

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Art. No.: 41700560

GTIN: 4026397539127



The article is no longer in our assortment.

Features:

- Compact and bright
- Equipped with 4 x 12 W HCL (hexacolor LED) in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- The device is cooled by passive convection cooling
- Control via stand-alone; W-DMX by wireless solution; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 22°

device

Logistic

EAN / GTIN: 4026397539127

Weight: 3,31 kg

Length: 0.22 m

Width: 0.20 m

Height: 0.25 m

- Cordless, flexible and versatile
- Battery operation up to 8,5h depending on program used

Package contents

- 1 x device, 1 x remote control

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	37 W
IP classification:	IP20
Lamp type:	LED lamp
Cooling:	Passive convection cooling
Control:	Stand-alone; W-DMX by wireless solution; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	33°
Housing color:	Black
Dimensions:	Width: 13,8 cm Depth: 14,5 cm Height: 19,1 cm
Weight:	2,91 kg
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 8,5h depending on program used Recharging time 4,5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Battery pack type:	Li-ion 14.8 V, 6600 mAh (97.68 Wh)
Battery operation:	8.5 hours
Recharging time:	4.5 hours
Battery remote control:	CR2025 button cell 3 V
DMX channels:	6/8/12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
LED type:	12 W HCL
LED number:	4
Beam angle:	22°
Dimensions (L x W x H):	145 x 138 x 191 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting