

EUROLITE AKKU IP UP-4 Entry QCL Spot QuickDMX

IP65 battery-powered uplight with RGBW LEDs, QuickDMX and IR remote control

Art. No.: 41700585

GTIN: 4026397691610



List price: 355.81 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 12h depending on program used
- 4 powerful LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; QuickDMX
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- Flicker-free
- With a beam angle of 16°
- OLED display
- Rubber feet
- Suitable for outdoor use IP65
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 2 x battery

Logistic

EAN / GTIN: 4026397691610

Weight: 4,90 kg

Length: 0.26 m

Width: 0.21 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack built-in Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; QuickDMX
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32
Housing color:	Black
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Width: 19,00 cm Depth: 15,50 cm Height: 23,25 cm
Weight:	4,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting