

EUROLITE LED KLS-180/6 Compact Light Set

Bar with 6 RGBW spots and 6 white strobe LEDs

Art. No.: 42109632

GTIN: 4026397690408



Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - Movable and tiltable spotlights
 - Dimmer electronic; color blend stepless; color change adjustable; colors preset
 - Strobe effect
 - The device is cooled by passive convection cooling
 - Control via IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Flicker-free
 - With a beam angle of 9°
 - 4 digit 7-segment LED display
 - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Suspended; on stand
- spotlight**
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
6 spots controlled separately
- bar**
- 6 LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately

Logistic

EAN / GTIN: 4026397690408

Weight: 7,60 kg

Length: 0.96 m

Width: 0.20 m

Heigh: 0.30 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 90 W

Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	2 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0.3 - 22 Hz
DMX channels:	3; 4; 6; 8; 9; 11; 21; 24; 29
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
PWM frequency:	2700 Hz
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18
Housing color:	Black
Attachment system:	Tube: 1x Ø 35mm
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 92.6 cm Depth: 14.6 cm Height: 26.7 cm
Weight:	6.00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
LED type:	4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	6 x 1 W SMD 8072 cold white (CW)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device
1 x bag
1 x remote control
1 x battery
1 x power cord
1 x user manual