

EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful 6in1 RGBWA/UV spots, QuickDMX support, IR remote control and carrying bag

Art. No.: 42109895

GTIN: 4026397657654



Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 7 LEDs 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
 spots controlled separately
- Dimmer electronic; color blend stepless; color selection; program selection
- UV effect
- 20 integrated show programs
- Direct color selection for 21 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 19°
- TV spigot
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397657654

Weight: 12,35 kg

Length: 1.32 m

Width: 0.15 m

Height: 0.39 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 2.5 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 10 W SMD 9090 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 128 cm Depth: 8 cm Height: 29 cm
Weight:	11.14 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x remote control
- 1 x bag
- 2 x omega bracket

4 x knurled screw
4 x washer
1 x battery
1 x terminating plug (power)