

## EUROLITE LED KLS-3002 MK2 Compact Light Set AIR

Art. No.: 42109896

Bar with 4 powerful 6in1 RGBWA/UV spots, AirW wireless system (2.4 GHz), wireless remote control and transport bag



**List price: 712.81 €**

incl. 19% VAT.

### Description:

The KLS 3002 delivers enough output to be used not only in party environments but also on concert stages. Its color mixing is based on red, green, blue, white, amber, and UV. This allows for vibrant, punchy colors as well as rich orange tones, soft pastels, and impressive blacklight effects.

As part of Eurolite's Air program, it features not only standard DMX control, but also an integrated wireless system. This enables system-wide control via a dedicated wireless remote, wireless master-slave operation and the use of an optional wireless foot switch.

### Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 28 LEDs 12 W SMD 5050 6in1 RGBWA/UV (homogenous color mix)<BR>4 spots controlled separately
- With a beam angle of 15°
- Spot effect; UV effect; strobe effect
- Dimmer electronic; color fade adjustable; color change adjustable; color blend stepless; color selection; program selection; program speed adjustable; color macros
- Direct color selection for 20 preset colors
- 20 integrated show programs
- Control via stand-alone; sound to light via microphone; master/slave function; rotary dial for brightness; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); AirW; wireless Master/slave function; wireless remote control; wireless footswitch (optional)

### Logistic

EAN / GTIN: 4026397750713

Weight: 12,40 kg

Length: 1.14 m

Width: 0.38 m

Height: 0.14 m

- 3 buttons on the remote control for saving your own settings
- DMX fail mode (blackout; hold; full on; auto)
- Flicker-free
- Monochrome 4 digit 7-segment LED display
- With omega bracket
- Silent operation
- The device is cooled by passive convection cooling
- For application areas such as: Wedding/gala/events; clubs/dancing school; mobile djs / entertainer; restaurants, bars and hotels; rental
- Application possibility: Suspended; on stand
- Mains input and output for power linking up to 8 units
- Fixtures available for Light Captain; Light´J; Colorchief
- Wireless remote control: operating range up to 30m in the open air
- AirW: operating range up to 70m with line-of-sight
- TV spigot

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	245 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version Bypass 2 x IEC connector (F) mounting version fused
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	28 x 12 W SMD 5050 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0.3 - 20 Hz
DMX channels:	2; 4; 6; 10; 24; 28; 32; 34
DMX input:	1 x 3-pin XLR (M) mounting version 1 x USB, type A
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; rotary dial for brightness; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); AirW; wireless Master/slave function; wireless remote control; wireless footswitch (optional)
Fixtures available for:	Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Range:	Wireless remote control: range up to 30m in the open air AirW: range up to 70m with line-of-sight
Carrier frequency:	2.4 GHz
Modulation:	GFSK
DMX fail mode:	Blackout; hold; full on; auto

Beam angle:	15°
Beam angle (1/2 peak):	15° multicolor
Beam angle (1/10 peak):	Spot 30°
Color temperature:	5700K
Housing color:	Black matte
Attachment system:	Pivot: 1x TV spigot Ø 28mm 2x omega bracket
Display type:	1 x monochrome 4 digit 7-segment LED display
USB port:	1 x type A
Material:	Metal, 1 mm, painted
Dimensions:	Length: 107.5 cm Depth: 5.5 cm Height: 28.7 cm
Weight:	11.30 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x 12 V 23AE alkaline manganese included
Carrier frequency:	433.92 MHz
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### Scope of delivery:

---

1 x device  
1 x user manual  
1 x declaration of conformity  
1 x power cord  
1 x remote control  
1 x bag  
2 x omega bracket  
4 x knurled screw  
4 x washer  
1 x battery  
1 x terminating plug (power)