

## EUROLITE LED KLS Scan Pro Next FX Compact Light Set

Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag

Art. No.: 42109898

GTIN: 4026397713138



### Features:

- Heart gobo for romantic occasions
  - Positioning within
  - Color wheel; gobo wheel with static gobos
  - Program selection; Dimmer electronic; color blend stepless
  - Strobe effect; multi beam effect; UV effect
  - Color wheel with 7 dichroic filters plus open
  - Gobo wheel with static gobos, 7 gobos and open
  - 20 integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
  - Flicker-free
  - The article is delivered with practical transport bag
  - The article is delivered pre-assembled
  - With mounting bracket
  - OLED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
  - Application possibility: Suspended; on stand
- spotlight**
- 5 LEDs 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)<BR>4 spots controlled separately
  - With a beam angle of 15°

### Logistic

EAN / GTIN: 4026397713138

Weight: 17,00 kg

Length: 1.17 m

Width: 0.56 m

Height: 0.18 m

**light effect**

- 2 LEDs 3 W R/G/B

**moving light**

- 1 LED 37.5 W cold white (CW)

**bar**

- 4 LEDs 1 W SMD 8072 ultra violet (UV)<BR> LEDs controlled separately

**Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	H05VV-F
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Housing color:	Black
Attachment system:	Tube: Ø 35mm 2x mounting bracket
Display type:	OLED display
Dimensions:	Length: 112 cm Depth: 10 cm Height: 42 cm
Weight:	13.30 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 1 W SMD 8072 ultra violet (UV)
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 30 lx, 3m: 4 lx, 6m: 1 lx
LED type:	2 x 3 W R/G/B
LED type:	5 x 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)
Beam angle (1/2 peak):	15°

Beam angle (1/10 peak):	30°
Illuminance in Lux (lx):	Spot red (R) 1m: 2300 lx, 3m: 235 lx, 6m: 58 lx Spot green (G) 1m: 4187 lx, 3m: 422 lx, 6m: 107 lx Spot blue (B) 1m: 760 lx, 3m: 78 lx, 6m: 20 lx Spot warm white (WW) 1m: 3290 lx, 3m: 325 lx, 6m: 85 lx Spot all 1m: 10283 lx, 3m: 1010 lx, 6m: 259 lx
LED type:	Each with 1 x 37.5 W cold white (CW)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **Scope of delivery:**

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x declaration of conformity
- 2 x mounting bracket
- 1 x remote control
- 1 x battery
- 1 x bag
- 2 x knurled screw
- 2 x washer