

EUROLITE LED PARty Spot Silent RGB/WW

Compact spotlight with 12 x 5 W 4in1 QCL RGB/WW LED and DMX control

Art. No.: 42110203

GTIN: 4026397722802



List price: 65.33 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
 - Color blend stepless; color change programs; Dimmer electronic
 - Strobe effect
 - 10 integrated show programs
 - Direct color selection for 20 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in LED PC-Control 512; EASY SHOW 2; EASY SHOW 3; Light´J; Light Captain; Colorchief
 - Flicker-free
 - With a beam angle of 12°
 - Good color rendering index (CRI)
 - With double bracket
 - 4 digit 7-segment LED display
 - For application areas such as: Party room; mobile djs / entertainer; small rental
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x light effect, 2 x mounting bracket, 2 x screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397722802

Weight: 0,68 kg

Length: 0.15 m

Width: 0.13 m

Height: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H03VVH2-F
Cable length:	Approx. 1 m
Device fuse:	T 1 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0,5 - 16 Hz
DMX channels:	4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 2; EASY SHOW 3; Light J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	2000 Hz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Color temperature:	2700K
Color rendering index (CRI):	83 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm
Weight:	0,60 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø13mm; 2 x Ø6mm
Material:	Metal, 1,5 mm
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting