

## EUROLITE LED Umbrella 140

Extraordinary RGB eye-catcher

Art. No.: 42111000

GTIN: 4026397625684



### Features:

- DMX-controllable lighting effect umbrella with 114 SMD RGB LEDs, distributed in 7 segments
- Segments can be controlled individually via DMX
- 6 segments make the surface of the umbrella shine, one segment in the middle shines directly at the audience
- Perfect as stage background and eye-catcher for decorative purposes in shops, display windows, fair stands, hotels, bars and clubs
- Can be mounted to a lighting stand or trussing - the umbrella's angle can be adjusted
- Easy transport (can be folded), setup and installation
- Covers a large area with a diameter of 140 cm
- Built-in auto and music show programs
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Stepless RGB color mixture, dimmer and strobe effect
- Addressing via control panel with 4-digit LED display
- Appropriate control unit included in the delivery
- Power connection via P-Con jack and included power cable with safety plug
- 114 LEDs SMD 5050 3in1 R/G/B (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free

### Logistic

EAN / GTIN: 4026397625684

Weight: 4,75 kg

Length: 1.02 m

Width: 0.29 m

Height: 0.29 m

## Technical specifications:

---

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 20 W  |
| Power connection:       | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  |
| Lamp type:              | LED lamp  |
| LED type:               | 114 x SMD 5050 3in1 R/G/B (homogenous color mix)  |
| DMX channels:           | 6; 24   |
| DMX input:              | 1 x 3-pin XLR (M) mounting version  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version  |
| Cooling:                | Passive convection cooling  |
| Control:                | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light´J; LED PC-Control 512; Light Captain  |
| Projection:             | Flicker-free  |
| Dimensions:             | Diameter: Ø 140 cm  |
| Weight:                 | 3.07 kg   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |

## Scope of delivery:

---

1 x omega bracket  
1 x device  
1 x user manual  
1 x power cord  
1 x multipin cable  
1 x umbrella