


EUROLITE LED FL-1300 Flamelight with DMX

DMX controlled flame effect with RGB LEDs, flame height 150 cm

Art. No.: 51114411 GTIN: 4026397625806



List price: 379.61 €

incl. 19% VAT.

Description:

DMX-contrallable flame effect with RGB LEDs, flame height 150 cm

The EUROLITE FL-1300 Flamelight creates decorative lighting effects on your stage. The 24 3 Watt RGB LEDs create an realistic effect, which you can also use for your exposition or other decoration possibilities.

The total flame height of the robust Flamelight FL-1300 is 150 cm.

You can control the FL-1300 in stand-alone mode or via DMX interface. Comfortable addressing and other settings are made via an integrated control unit with LED display and four operating keys. Of course, you can also remotely control the device with the included remote control.

The Flamelight has several functions. These include Dimmer, auto modes and speed settings. A cold appliance power cable with safety plug is included in the package.

Features:

- Unbelievably realistic effect
- Flame height: 150 cm
- Robust version
- Two fans
- 24 powerful LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
- Color change adjustable; color fade adjustable; Dimmer electronic
- Control via stand-alone; DMX; wireless remote control
- 4 digit 7-segment LED display
- For application areas such as: Wedding/gala/events; mobile use; restaurants, bars and hotels
- Application possibility: Standing

Package contents

Logistic

EAN / GTIN: 4026397625806

Weight: 9,25 kg Length: 0.53 m Width: 0.26 m Heigth: 0.38 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
LED type:	24 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; wireless remote control
Beam angle (1/2 peak):	10°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Material:	Metal
Dimensions:	Width: 52,5 cm Depth: 23,8 cm Height: 34,5 cm
Weight:	8,45 kg
Noise classification:	Class 4 (loud noises)
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,2 m
Flame cloth	
Color:	White
Dimensions:	Height: 140 cm
Remote control	
Battery:	1 x 12 V AR23 zinc air built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting