

EUROLITE NH-50 DMX Fazer

Compact DMX fazer with WirelessDMX port & adjustable output angle

Art. No.: 51701954 GTIN: 4026397739312











List price: 213.01 €

incl. 19% VAT.

Features:

- Produces fine, translucent haze without nebulizing the room at the same time
- Ideal for accentuating light and laser beams
- Vertically adjustable output angle for a perfect fog distribution
- Auto temperature control
- Short warm-up time
- Output distance: Approx. 2,0 m
- With level indication
- Operates on water-based fluid
- Removable, backlit tank
- Control via DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

 1 x device, 1 x user manual, 1 x container, 1 x filter, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 2 x washer

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	Approx. 500 W

Logistic

EAN / GTIN: 4026397739312

Weight: 3,87 kg Length: 0.33 m Width: 0.26 m Heigth: 0.28 m

IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, F 4 A fuse replaceable
Warm-up time:	Approx. 1,5 min
Output volume:	Approx. 170 m³/min
Output distance:	Approx. 2,0 m
Output duration:	- continuous
Tank capacity:	1,3 I water-based fluid removable, backlit tank
Fluid consumption:	Faze mode approx. 5,7 ml/min
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Housing color:	Black matte
Attachment system:	Mounting bracket
Operating principle:	Vaporizing fog machine with air compressor
Display type:	1 x monochrome 4 digit 7-segment LED display
Controls:	Overheat
Material:	Metal, painted
Dimensions:	Length: 30 cm Width: 18,5 cm Height: 29,5 cm
Weight:	3,53 kg
Power cord	
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, painted