

EUROLITE NSF-350 LED Hybrid Spray Fogger

DMX fog machine with 1500 W, LED illumination, vertical fog output

Art. No.: 51701977 GTIN: 4026397513387











List price: 474.81 €

incl. 19% VAT.

Features:

- LED light effect with fog spouter in one device
- Your all-in-one solution with powerful vertical smoke output
- Output nozzle with RGB LED illumination for impressive effect presentations
- Additional button for manual activation
- 21 powerful LEDs 3 W R/G/B
- Color selection; color change adjustable
- Strobe effect
- Output distance: Approx. 6 m
- With level indication
- Operates on water-based fluid
- Removable tank
- Control via DMX; stand-alone; wireless remote control
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- For application areas such as: Stage; theater; rental
- Application possibility: Standing

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x transmitter, 1 x declaration of conformity, 1 x container, 1 x filter, 1 x battery

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1500 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397513387

Weight: 9,20 kg Length: 0.51 m Width: 0.38 m Heigth: 0.27 m

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
LED type:	21 x 3 W R/G/B
Warm-up time:	Approx. 5 min
Output volume:	Approx. 1130 m³/min
Output distance:	Approx. 6 m
Tank capacity:	2,5 I water-based fluid removable tank
Fluid consumption:	Approx. 95 ml/min
DMX channels:	8
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	DMX; stand-alone; wireless remote control
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Housing color:	Black
Controls:	Low fluid
Color:	Black
Dimensions:	Width: 41 cm Depth: 63,5 cm Height: 20,5 cm
Weight:	7,90 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Remote control	
Battery:	1 x 12 V LR27 alkaline manganese built-in
Carrier frequency:	433,920 MHz