

EUROLITE NB-150 ICE Low Fog Machine

Simple floor fogger with 1500 W, remote control, ice cube cooling

Art. No.: 51701983

GTIN: 4026397638608



Description:

Simple floor fogger with 1500 W, remote control, ice cube cooling

The EUROLITE NB-150 ICE ground fogger produces large quantities of low-lying ground fog. It is ideal for stages and discotheques. The NB-150 ICE can score points with its short warm-up time and low fluid consumption. It works with conventional fog fluid and ice cube cooling.

To obtain 25 minutes of continuous fog at full output, you need to fill the ground fogger with four kilograms of ice cubes. You can easily empty and clean the NB-150 ICE via the drain. The tank is removable.

The fog effect is triggered by DMX or via the integrated control module with LCD display. Alternatively, you can easily control the ground fogger with the wired remote control.

You can easily adjust the temperature with the thermoswitch. Intervals, duration and fog quantity can also be variably adjusted according to your requirements.

The sturdy metal housing is equipped with carrying handles and transport castors.

Features:

- Low fluid consumption rate
- 4 kg ice cubes allow for 25 minutes continuous fogging at 100 % output
- Adjustable timer with interval, duration and output volume
- Continuous output
- Water drainage valve system allows for easy cleanup
- Linking and synchronized control via 5-pin XLR connectors
- Rugged metal housing

Logistic

EAN / GTIN: 4026397638608

Weight: 22,20 kg

Length: 0.75 m

Width: 0.47 m

Height: 0.46 m

- Short warm-up time
- Output distance: Approx. 5 m
- Operates on water-based fluid
- Removable tank
- Control via DMX; stand-alone; wired remote control
- Fixtures available for LED PC-Control 512
- Monochrome LCD display
- For application areas such as: Wedding/gala/events; stage; theater; video and photography
- Application possibility: Standing

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1500 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	2.5 m
Warm-up time:	Approx. 4 min
Output distance:	Approx. 5 m
Tank capacity:	2 l water-based fluid removable tank
Fluid consumption:	Approx. 25 ml/min
Ice chamber:	4 kg
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; wired remote control
Fixtures available for:	LED PC-Control 512
Housing color:	Silver
Display type:	Monochrome LCD display
Controls:	Overheat
Dimensions:	Width: 36 cm Depth: 68 cm Height: 42 cm
Weight:	19.75 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x container
- 1 x filter