

EUROLITE WLF-1500 Water Low Fog PRO

DMX machine installed in a sturdy case creates water-based floor fog

Art. No.: 51701993 GTIN: 4026397649413











List price: 1545.81 €

incl. 19% VAT.

Features:

- No CO2 or dry ice is necessary due to ultrasonic technology, therefore inexpensive to operate
- Extremely easy to handle
- Integrated in a flightcase, makes the machine tough, durable and easy to carry
- Inner, essential components made of stainless steel
- Concentrated and steady fog output
- Adjustable timer with interval, duration and output volume
- Continuous output
- Very low fluid consumption rate
- Water drainage valve system allows for easy cleanup
- Short warm-up time
- Output distance: Approx. 2 m
- With level indication
- Operates on water-based fluid
- Removable, backlit tank
- Big tank capacity
- Control via DMX; wireless remote control; timer
- Preprogrammed in LED PC-Control 512; Light Captain
- Monochrome LCD display
- For application areas such as: Wedding/gala/events; stage; theater; video and photography;
- Application possibility: Standing

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x tube, 1 x declaration of conformity, 1 x frame, 1 x battery

Logistic

EAN / GTIN: 4026397649413

Weight: 37,70 kg Length: 0.71 m Width: 0.45 m Heigth: 0.58 m Bulky product

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1400 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 3 min
Output distance:	Approx. 2 m
Tank capacity:	1,8 I water-based fluid removable, backlit tank 6,7 I water fixed tank
Fluid consumption:	Approx. 13 ml/min
DMX channels:	1
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Control:	DMX; wireless remote control; timer
Preprogrammed in:	LED PC-Control 512; Light Captain
Housing color:	Black
Heater:	1000 W
Display type:	Monochrome LCD display
Controls:	Low fluid; overheat
Color:	Black
Dimensions:	Width: 41,5 cm Depth: 68 cm Height: 52 cm
Weight:	34,65 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x 12 V LR27 alkaline manganese built-in
Carrier frequency:	433,920 MHz