

EUROLITE WLF-2500 Water Low Fog PRO

Extremely powerful floor fogger in a case with ultrasonic technology

Art. No.: 51702062

GTIN: 4026397673197



List price: 2497.81 €

incl. 19% VAT.

Description:

The WLF-2500 ground fog machine creates enormous amounts of low lying fog for stage and theater productions, film sets, large clubs and discotheques. The machine uses ultrasonic technology to atomize tap water and mix it with vaporized fog fluid. It generates a fine ground mist without the need for harmful CO2 or dry ice as a cooling component. Therefore the operating costs are low and the machine is environmentally friendly and safe to use.

Logistic

EAN / GTIN: 4026397673197

Features:

Extremely powerful floor fogger in a case with ultrasonic technology

- The water is atomized by ultrasound and mixed with the fog particles
- Ultrasonic atomizer can be switched off for standard fog machine operation
- Solid flightcase with swivel wheels
- 2 flexible fog hoses with quick connectors
- Adjustable timer with interval, duration and output volume
- Very low fluid consumption rate
- Water drainage valve system allows for easy cleanup
- For the best effect please use Eurolite DSA fog fluid
- Short warm-up time
- Output distance: Approx. 2,5 m
- With level indication
- Operates on water-based fluid
- Removable tank
- Big tank capacity
- Control via DMX; wireless remote control; timer

- Monochrome LCD display
- For application areas such as: Wedding/gala/events; stage; theater; video and photography
- Application possibility: Standing

EUROLITE WLF-2500 Water Low Fog PRO (machine with case)

- Short warm-up time
- Output distance: Approx. 2,5 m
- Operates on water-based fluid
- Big tank capacity
- Control via DMX; wireless remote control; timer
- Monochrome LCD display

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x declaration of conformity, 2 x container, 2 x filter, 1 x battery

EUROLITE WLF-2500 Water Low Fog PRO (Fog Hose and adapter)

- Rugged carrying handle

Package contents

- 2 x adapter, 2 x tube, 4 x mounting material

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	2500 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 3 min
Output distance:	Approx. 2,5 m
Tank capacity:	1,8 l water-based fluid removable tank 18 l water removable tank
Fluid consumption:	Approx. 17 ml/min
DMX channels:	1
Control:	DMX; wireless remote control; timer
Carrier frequency:	433 MHz
Housing color:	Black
Display type:	Monochrome LCD display
Color:	Black
Dimensions:	Width: 61 cm Depth: 80 cm Height: 60 cm
Weight:	55,05 kg
Noise classification:	Class 2 (slight noise)

EUROLITE WLF-2500 Water Low Fog PRO (machine with case)

Power supply:	230 V AC, 50 Hz
Power consumption:	2500 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Warm-up time:	Approx. 3 min
Output distance:	Approx. 2,5 m
Tank capacity:	1,8 l water-based fluid 18 l water
Fluid consumption:	Approx. 17 ml/min
DMX channels:	1
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Control:	DMX; wireless remote control; timer
Carrier frequency:	433 MHz
Housing color:	Black
Display type:	Monochrome LCD display
Controls:	Low fluid
Color:	Black
Dimensions:	Width: 61 cm Depth: 80 cm Height: 60 cm
Weight:	49,55 kg
Remote control	
Battery:	12 V LR27 alkaline manganese built-in

EUROLITE WLF-2500 Water Low Fog PRO (Fog Hose and adapter)

Weight:	4,75 kg
Adapter	
Housing color:	Black
Carrying handle:	1 pc/pcs
Dimensions:	Length: 32 cm Width: 35 cm Depth: 19 cm
Weight:	1,83 kg
Tube	
Color:	Black
Dimensions:	Length: 300 cm Diameter: Ø 12 cm
Weight:	0,48 kg