

EUROLITE PolarStar RGB Laser

Star laser for colored and white star effects and LED northern light effect

Art. No.: 51741069

GTIN: 4026397743647



List price: 355.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 7 W SMD 8072 3in1 TCL RGB
- Animation wheel rotating
- Dimmer electronic
- Laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- 3 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 23°
- With mounting bracket
- 3 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397743647

Weight: 1,85 kg

Length: 0.30 m

Width: 0.25 m

Height: 0.14 m

Technical specifications:

| | |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 20 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug |
| Cable length: | 1,4 m |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 7 W SMD 8072 3in1 TCL RGB |
| Flash rate: | 0,5 - 20 Hz |
| Equipment: | Animation wheel rotating |
| Laser class: | 2M |
| Laser color: | R/G/B |
| Laser module: | R/G/B 193 mW |
| DMX channels: | 8 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| PWM frequency: | 23500 Hz |
| DMX fail mode: | Hold; blackout |
| Beam angle: | 23° |
| Beam angle (1/2 peak): | 23° |
| Housing color: | Black |
| Attachment system: | 3x Ø 10mm Mounting bracket |
| Display type: | 3 digit 7-segment LED display |
| USB port: | Type A |
| Material: | Aluminum |
| Dimensions: | Width: 24,0 cm Depth: 20,5 cm Height: 16,5 cm |
| Weight: | 1,62 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |