

EUROLITE LED KLS Laser Bar Next FX Light Set

Bar with powerful spots, UV strobe LEDs, laser (RG, 2M), QuickDMX port and carrying bag

Art. No.: 51741094

GTIN: 4026397684681



Features:

- 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - Compact lightweight
 - Crossbar with integrated DMX control unit and TV spigot for tripod installation
 - When fog is used, this effect becomes especially attractive
 - Dimmer electronic; color blend stepless; program selection
 - 26 integrated show programs
 - The device is cooled by cooling fan
 - Control via DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
 - TV spigot
 - With mounting bracket
 - 3 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
 - Application possibility: On stand
- laser**
- Laser
 - Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 4 W SMD 9080 4in1 RGB/WW (homogenous color mix)
4 spots controlled separately
 - With a beam angle of 7°
- light effect**

Logistic

EAN / GTIN: 4026397684681

Weight: 11,90 kg

Length: 1.12 m

Width: 0.20 m

Height: 0.51 m

- 4 LEDs 3 W SMD 8072 R/G/B/WW
 lighting effects controlled separately
 - Multi beam effect; fan effect; flower effect
- bar**
- 4 LEDs 1.5 W SMD 8072 ultra violet (UV)
 LEDs controlled separately
 - UV effect; strobe effect

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	6; 8; 11; 21; 25; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	3 digit 7-segment LED display
Dimensions:	Width: 111 cm Depth: 15 cm Height: 41 cm
Weight:	10.50 kg
Noise classification:	Class 2 (slight noise)
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	4 x 3 W SMD 8072 R/G/B/WW
LED type:	3 x 4 W SMD 9080 4in1 RGB/WW (homogenous color mix)
Beam angle (1/2 peak):	Spot 7°
Beam angle (1/10 peak):	Spot 20°
LED type:	4 x 1.5 W SMD 8072 ultra violet (UV)
Flash rate:	0 - 30 Hz

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x bag
- 1 x declaration of conformity
- 1 x remote control
- 2 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x terminating plug (power)