

EUROLITE LED TMH-W63 Moving Head Zoom Wash

Washlight with 7 x 9 W LEDs, 4in1 QCL RGBW-Farbmischung and motorized zoom

Art. No.: 51785885

GTIN: 4026397672695



List price: 355.81 €

incl. 19% VAT.

Features:

- 7 powerful LEDs 9 W high-power 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN, 195° TILT
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Motion macros adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 6° - 29°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; small rental
- Application possibility: Suspended; standing

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397672695

Weight: 4,75 kg

Length: 0.27 m

Width: 0.27 m

Height: 0.34 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 100 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 7 x 9 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 195° exact positioning (16 bit resolution) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) |
| Flash rate: | 2,5 - 18 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 15 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| PWM frequency: | 2900 Hz |
| Beam angle: | 6° - 29° |
| Beam angle (1/2 peak): | 6 - 18° |
| Beam angle (1/10 peak): | 11 - 29° |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 7863 lx, 3m: 1074 lx, 6m: 269 lx Narrow green (G) 1m: 15691 lx, 3m: 2179 lx, 6m: 549 lx Narrow blue (B) 1m: 2497 lx, 3m: 406 lx, 6m: 103 lx Narrow cold white (CW) 1m: 17115 lx, 3m: 2398 lx, 6m: 605 lx Narrow all 1m: 40258 lx, 3m: 5714 lx, 6m: 1432 lx Wide red (R) 1m: 1586 lx, 3m: 187 lx, 6m: 49 lx Wide green (G) 1m: 3083 lx, 3m: 385 lx, 6m: 101 lx Wide blue (B) 1m: 568 lx, 3m: 73 lx, 6m: 20 lx Wide cold white (CW) 1m: 3372 lx, 3m: 407 lx, 6m: 106 lx Wide all 1m: 8103 lx, 3m: 994 lx, 6m: 257 lx |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |

| | |
|-----------------------|--|
| Dimensions: | Width: 21,0 cm |
| | Depth: 16,0 cm |
| | Height: 29,5 cm |
| Weight: | 4,15 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |